


EVCE-SV6-08-2NO

2-way ,2-position

Normally Open Bidirectional Blocking



Technical Specifications

Operating Pressure :	350Bar
Flow :	50L/min
Internal leakage :	5 drops/min at 350bar
Operating temperature :	-30°C to+ 120°C (- 22°F to+ 250°F)
Cavity :	VC08-2
Fluids:	Mineral based or synthetic hydraulic fluid with lubricating properties
Fluid viscosity range :	7.4 to 420cSt.


Features

- Hardened seat for long life
- Compact size
- Industry common cavity
- Continuous-duty rated solenoid
- Optional coil voltages and terminations

Operation

When de-energized, the poppet allows flow in both directions. When energized, the valve blocks flow in both directions

Symbol



Order Codes

	Base Model	Normally Open	Option	Seals	Voltage	Coil Connection
	EVCE - SV6-08-2	NO	Table 1	Table 2	Table 3	Table 4
Example	EVCE - SV6-08-2	NO	M	B	24	H

Table 1

Code	Option
Blank	Not Manual
M	Manual Emergency

Table 3

Code	Voltage
12	12VDC
24	24VDC
110	110VAC
220	220VAC


Table 2

Code	Seals
B	NBR
V	FKM

Table 4

Code	Coil Connection
H	DIN43650
F	Deutsch DT04-2P
A	Amp Plug
D	Double Lead
S	Single Lead

Performance Curves



Installation Dimensions

